

COUNCIL REPORT

TO: CITY MANAGER

DATE: 2009 MARCH 18

FROM: DIRECTOR PLANNING & BUILDING FIRE CHIEF

SUBJECT: SIX STOREY WOOD-FRAME RESIDENTIAL BUILDINGS

PURPOSE: To provide Council with information and recommendations on the B.C. Building Code changes allowing the construction of six storey wood-frame residential buildings.

RECOMMENDATIONS:

- 1. **THAT** rezonings for the development of five or six storey wood-frame buildings only proceed after the concerns outlined in this report have been satisfactorily addressed.
- 2. THAT Council authorize an amendment to the Building Bylaw to include Building Specialists in the definition of Registered Professionals enabling the Chief Building Inspector to require Building Specialists for the design and field review of the construction of complex buildings.
- **3. THAT** a copy of this report be sent to Honourable Rich Coleman, Minister of Housing and Social Development, requesting that the issues outlined in this report be addressed for inclusion in the B.C. Building Code.

REPORT

1.0 BACKGROUND

At the regular Council meeting of 2009 February 02, Council directed staff to provide a report on the B.C. Building Code (Code) changes allowing the construction of six storey wood-frame residential buildings. The purpose of this report is to outline the Code changes, issues arising from those changes and the impact of those changes in Burnaby.

On 2008 February 16, the Thorne Speech indicated that "we will lead the way in safe, six storey wood-frame construction that lowers building and housing costs." Premier Gordon Campbell also indicated that he wanted to support the province's forest industry by allowing higher wood-frame buildings.

In 2008 May, Housing Minister Rich Coleman announced the Province's intention to increase the maximum height for wood-frame residential buildings from four to six storeys by amending the Code.

In 2008 June, the Building and Safety Policy Branch, a branch of the Office of Housing and Construction Standards responsible for the development of the Code, started working on the Code changes. In 2008 August, the Branch hired consultants to conduct research, identify the issues to be addressed and propose Code changes to allow the construction of six storey wood-frame residential buildings.

Between 2008 July and November, staff in the Building and Safety Policy Branch worked with stakeholders to develop proposed changes to the Code. Public consultation on the proposed Code changes was conducted from 2008 November 15 to December 15.

In general, the stakeholders felt that their input was hampered by time constraints and limited background information and research. Some of the important issues outlined in this report have not been addressed and recommendations were not incorporated in the Code changes.

2.0 NEW BUILDING CODE PROVISIONS

The following new Code provisions, for residential buildings only, were enacted by Ministerial Order on 2009 January 08 and will take effect on 2009 April 06:

2.1 Building Height

The current Code permits wood-frame residential buildings up to four storeys in height. The Code changes increase the allowable height of these buildings to six storeys with a maximum dimensional height of 18 meters to the uppermost storey. The height limit of 18 meters is also the current limit for a building that would not be considered as a high-rise building.

However, in higher seismic zones, such as the Lower Mainland, the current structural requirements of the Code for wood-frame construction limit the building height between to 15 m and 20 m depending on the types of wood shear walls used to resist seismic forces. This requirement may further restrict the dimensional height and the number of storeys that can be built.

2.2 Building Area

The Code addresses the inherent difference between combustible and non-combustible construction by limiting combustible building area to 20% of that permitted for a non-combustible building of similar height. This factor is maintained with the Code changes. The building area defines the total permissible area for each floor.

The Code currently employs a formula in apportioning building area relative to the building height, such that the resulting gross floor area of all the floors is limited to a maximum of 7200 sq.m.

The current maximum area for each floor of a four storey wood-frame building is 1800 sq.m. The new maximum floor area is 1440 sq.m. for a five storey building and 1200 sq.m. for a six storey building.

By retaining the same gross floor area, the intent of the Code change is to maintain the same volume of combustible construction.

2.3 Exterior Cladding

Combustible cladding is currently permitted on a four storey residential building. The Code change limits the cladding for five storey and six storey wood-frame residential buildings to three types:

- non-combustible material,
- combustible material with certain fire-resistance, or
- fire-retardant treated wood.

The intent of the Code change is to address the risk of fire spreading up the building face.

2.4 Sprinkler System

Currently a four storey wood-frame residential building is required to have a sprinkler system conforming to NFPA 13R, "Installation of Sprinkler Systems in Residential Occupancies up to and Including Four Stories in Height," The Code change requires five storey and six storey buildings to have a sprinkler system conforming to a higher standard, NFPA 13. Additional sprinkler protection will apply to balconies, closets, attic and crawl spaces.

2.5 Seismic Design

Shear walls provide resistance to lateral earthquake loads. The Code change requires the shear walls of all floors to line up over the entire height of the building. Offset or discontinuity of the shear walls weakens the structural capacity of the building structure to resist lateral earthquake loads.

3.0 ISSUES

Although the stakeholders and the public generally support the principle of allowing the construction of six storey wood-frame buildings and the Code changes do address some of the concerns raised, a number of significant technical and process issues remain. They are discussed as follows:

3.1 Technical Issues

This Section identifies technical issues and concerns that have not been addressed by the Code changes for various reasons. Municipalities have limited power under the Concurrent Authority within the Community Charter to establish bylaws that alter the technical standards or the application of the Code without the approval of the Minister.

The Charter limits municipalities to process oriented issues in relation to the Codes administration.

3.1.1. Lack of Research on Seismic Design

Code changes of this magnitude that require extensive research, testing, consultation and the development of education and training documents would normally take several years to complete. These Code changes were completed in six months. The Building and Safety Policy Branch started to work on the Code changes in 2008 June and hired two consultants in 2008 August to review primarily structural performance and fire risks inherent in six storey wood-frame buildings. The proposed changes were available for public consultation between 2008 November 15 and December 15 and were approved by the Minister in 2009 January.

The Association of Professional Engineers and Geoscientists of BC (APEGBC) and the Architectural Institute of BC (AIBC) identified a number of concerns related to issues such as fire safety, structural adequacy and material shrinkage, and stated that there was insufficient time to develop guidelines for their members prior to the implementation of the Code changes. APEGBC has submitted a proposal for funding from the Province to produce the necessary guidelines, however, the initial request was not approved. Recently the Province agreed to fund a shortened version to approximately 1/4 of the original proposal.

The Province also provided funding to Forintek, a research group, to test a six storey woodframe building on an earthquake shaker table in Japan this summer. Forintek is also conducting some research on the structural design of six storey wood-frame buildings, both in their laboratory at the University of British Columbia and at the Colorado State University. The results are not expected to be available prior to the effective date of the Code changes in April.

Code requirements pertaining to buildings and construction materials provisions have evolved based on research and historical experience of the performance of wood-frame buildings up to four storeys. It is the view of staff that more research and consultation should be required prior to adopting the Code changes which allow an increase in the building height of wood-frame buildings to six storeys.

3.1.2. Fire Risks

Recommendations of the consultants addressing fire risks and concerns expressed by interest groups such as the Building Officials, Fire Chiefs, Professional Engineers and Architects, were not incorporated in the Code changes. Such recommendations are listed as follows:

- Increase the reliability of the fire separations between floors by using two layers of fire-rated drywalls instead of one layer;
- Limit the risk of fire spread up the exterior of the building by only allowing noncombustible cladding (and not permitting combustible materials);
- Limit the risk of fire spread up the interior of the building by providing fire blocking of vertical concealed spaces;

- Provide better exit routes by requiring non-combustible exit shafts; and
- Aide firefighting by providing high-rise measures, such as a firefighters' elevator, a voice communication system, a smoke control system and an emergency generator

The Code changes failed to address a concern pertaining to residential buildings for seniors and for assisted living. The occupants in those buildings would have difficulty negotiating six storeys of stairs in the event of an emergency.

Fire spread in wooden structures, regardless of sprinklers, is considerably more rapid than in those built of non-combustible materials (i.e. concrete). In many cases, multi-storey wooden structures have experienced catastrophic fire loss between the firewalls, along with considerable damage to the rest of the building as a direct result of the rate of fire spread. There can be a dozen or more units between the firewalls and fire intensity contributing to radiant, conductive and convective heat transmission can seriously affect their ability to stop the horizontal spread of the fire.

In a concrete building, the fire is usually contained to the area of origin and rarely spreads to other floors or units. The areas or units in concrete structures act as compartments and greatly reduce the spread of fire. If the fire is not in or affecting the safety of their unit, the occupants can stay where they are and wait for rescue if they are unable to access a fire escape route.

In a wooden structure, this is not an option. The occupants must escape the building. The potential rate of fire spread in a wood-frame building greatly reduces the time someone has to find their way out of the building. Escaping from a sixth floor is going to take longer than it does to escape from a fourth floor. This applies to firefighter escape as well.

The Code changes did not address these fire issues and may put the firefighters and the occupants of six storey wood-frame buildings at an increased risk.

3.1.3. Fire Fighting

Six storey structures require the use of high-rise firefighting tactics which are much different from those used for low-rise structures (1 - 4 storeys). The current three and four storey wooden structures create demanding challenges when fighting fires from an external upper floor access perspective. The transition from low-rise to high-rise firefighting tactics takes place for anything greater than three storeys above ground level. Firefighters are able to access third floor balconies with ground ladders but require truck aerial ladders to reach higher storeys. It is both the number of storeys and the building height from any side that determine the specific firefighting tactics used. Fires in these structures are fought using internal as well as external tactics and each complements the other. Access for aerial devices is usually an issue in apartment complexes and which floor the firefighters can get to is dependent on how close they can get to the building. As a result, internal firefighting tactics may be the only option for fires in the upper floors, a much more dangerous situation in a wooden structure than one constructed of non-combustible materials.

Fires in concrete buildings are usually compartmentalized, in other words they are contained to a cubicle like area. In concrete buildings, firefighters can attack the fire from outside the fuel load area that is burning, even if it is an inside hallway or stairwell. When fighting fire from the inside of a wooden building, they usually find themselves operating in the middle of the fuel load.

A critical component of any firefighting strategy includes searching the building for occupants requiring rescue. A six storey wooden building would take about twice the time to search as compared to a three storey building with the same available resources. With the potential of a more rapid fire spread, time becomes much more critical. A wood-frame building would require a complete initial search, while in comparison, a high-rise building constructed of non-combustible materials only requires an initial search of the immediate floor or two above the fire floor and occupants can remain in their unit if it is unsafe to exit the building.

It is common for fires in low-rise (up to 4 storeys) wood-frame apartment buildings to require more firefighting resources for a longer period of time to extinguish than for those in multistorey structures constructed of non-combustible materials enclosing each unit. It is the potential for the rapid spread of the fire to the entire structure as well as the surrounding exposures that determines the resources assigned to the incident. Fires in wooden multi-unit apartment structures usually require responses that tax the fire fighting resources to the limit and often require the callback of off-duty personnel to support the operation and provide coverage for the remainder of the city.

3.1.4. Building Envelope

There is no additional provision in the Code changes to address the design and performance of the building envelopes of six storey wood-frame buildings. The consultants hired by the Province have cited the reason that Part 5 of the current Code, Environmental Separation, is objective-based and adequately deals with the building envelopes for buildings of different heights. It is therefore incumbent on the designer to consider the increased risks, and design accordingly.

The design and construction of building envelopes are very complex. Factors affecting the performance of the envelope of a building include knowledge and experience of the designer, detailing of the interfaces between different materials, workmanship, field reviews by the professionals and maintenance by the owners. The level of competency and knowledge of the industry and the design professionals and the standard of drawings and documents vary substantially within the industry.

Given the above factors, together with the amount of rainfall in the Lower Mainland, the addition of two extra wood-frame storeys could increase the risk of building envelope failure.

3.1.5. Material Shrinkage

There is no specific provision in the Code changes to deal with the shrinkage of wood products used in the construction of six storey wood-frame buildings.

The only reference to shrinkage is made in the Appendix of the Code that warns the designers that building movement, due to shrinkage, should be considered in the designs of cladding systems, mechanical and plumbing systems, hold-down devices for structural walls and connections to non-shrinking elements, including firewalls and elevator shafts.

3.2 Process Issues

Administrative matters may be dealt with autonomously at the local government level. Building Bylaw that establishes procedures for the administration and enforcement of the Code, such as plan review and building inspection, is not subject to concurrent authority and does not require the Minister's approval. Some of these process issues identified below may be addressed at the local government level.

3.2.1 Qualification of Professionals

Since the current Code is objective-based, it heavily relies on the design professionals to use their knowledge and experience to ensure that their design meets the objectives of the Code. One of the major concerns identified by various interest groups and the consultants hired by the Province was the need for qualified design professionals to address the technical issues identified above (fire safety, structural, building envelope and material shrinkage).

Currently, the Code requires registered architects and professional engineers to design and provide construction field reviews of six storey wood-frame residential buildings. However, the Code does not require specific training, knowledge or experience for the professionals. The certification and regulation of the practice of architects and engineers are left to AIBC and APEGBC under the authority of their respective Acts.

The Ministry of Housing and Social Development introduced Bill 10, The Housing Statues Amendment Act, on 2008 April, providing the two professional associations with authority to create categories of Building Specialists and set qualifications. It also enables the local governments to require Building Specialists, created by the two associations, to certify plans submitted for Building Permits. This provides local government with confidence that new and complex technologies are safely and effectively implemented.

APECBC has already created a category of Building Specialist called "Designated Structural Engineers" (DSE) for structural design of more complex buildings, such as those classified as Part 3 buildings by the Code. The City of Vancouver has already amended their Building Bylaw requiring DSE for all Part 3 buildings since 2007.

AIBC and APECBC are jointly working to create two more categories of Building Specialists, "Building Envelope Professionals" (BEP) for the design and field review of building envelopes and "Certified Professionals" (CP) to coordinate the permit and inspection processes. The program for BEP may be completed this year while the one for CP may take two years to finish.

The current Burnaby Building Bylaw requires that the design and field review of building envelope of a residential building, other than single and two family dwellings, shall be carried out by a Building Envelope Professional that meets the qualifications as prescribed in the Building Bylaw.

The Burnaby Building Bylaw also provides the authority to the Chief Building Inspector to require the owner to obtain the design and field review services of a "Registered Professional", an architect or a professional engineer, in respect of a permit for a building that, in the opinion of the Chief Building Inspector, the site conditions, size or complexity of a building or an aspect of a building so warrants.

In order to take advantage of the authority provided by Bill 10, it is recommended that Council authorize the amendment of the Burnaby Building Bylaw to include Building Specialists, as defined in Section 55(1) of the Community Charter, in the definition of Registered Professionals.

This amendment will enable the Chief Building Inspector to require certification of Building Specialists, such as Designated Structural Engineers, Building Envelope Professionals and Certified Professionals, for complex buildings such as all Part 3 which includes the six storey wood-frame buildings.

The benefit of this bylaw change is not only to ensure that the new and complex technologies are safely and effectively implemented but also reduces the City's liability exposure in future claims due to faulty construction.

3.2.2 Qualification of Contractors and Trades

Concerns were raised by building officials and design professionals that some of the contractors and trades do not have the experience, qualifications and/or ability to construct four storey woodframe buildings, particularly in relation to building envelopes, fire stop systems, material shrinkage due to moisture content of wood and shear walls. Construction of six storey buildings will exaggerate the need for qualified contractors and trades.

Currently there is no mandatory qualification for contractors or trades that are responsible for the items mentioned above. The new home warranty program relies on the insurance providers to screen the general contractors; however, the insurance providers qualify contractors based more on their financial ability than their technical ability.

APEGBC's preliminary proposed design guideline for structural engineers recommended that contractors should be qualified by their past experiences or be able to demonstrate to the engineer that they have the necessary understanding and competencies to perform the work including proper installation of all details provided by the structural engineer.

Qualification of contractors and trades is a provincial matter, however, we are able to require, under our current Building Bylaw, an independent third party inspection in addition to the inspections provided by our building inspection staff to ensure certain critical building components are being installed correctly.

3.2.3 Education and Training

APEGBC is currently working on a design guideline for professional engineers to address the six storey wood-frame buildings. The guideline will be a scaled down version from the original proposal due to funding and time restraints. The guideline will cover topics such as design, drawing and review practice, shear walls, shrinkage, firewalls and elevator shafts, and hybrid systems with mix use of wood, steel, concrete and masonry.

APEGBC is hoping to have the guideline available to the engineers on or before the effective date of the Code changes. However, time would still be required to schedule seminars for education and training. It is not expected that the training would be completed until later this year.

Unfortunately, there is no specific education and training program for building officials, contractors and trades at this time.

4.0 IMPACT OF CODE CHANGES IN BURNABY

4.1 Zoning

Five and six storey wood-frame residential buildings could be accommodated through Comprehensive Development rezoning under Burnaby's existing zoning bylaw, if approved by Council.

Although the RM2 and RM3 zoning districts permit a maximum building height of three storeys, four storey residential buildings have been permitted under Comprehensive Development zoning based on these districts, at a maximum RM3 density of 1.10 Floor Area Ratio with underground parking and no amenity bonus.

Six storey residential buildings would hypothetically tend to fall within the RM4 and RM5 density range, i.e. 1.70 and 2.20 Floor Area Ratio maximums respectively (with underground parking and no amenity bonus). Given the maximum lot coverage of 25 percent and 30 percent permitted in the RM4 and RM5 districts respectively, the maximum Floor Area Ratios permitted in these zones could not be achieved in a six storey building form, except through a Comprehensive Development rezoning which increased the permitted lot coverage for a specific development.

Given the concerns outlined in this report, it is unlikely that rezoning applications for six storey wood-frame apartment buildings would be supported by staff until such time as the issues outlined in this report are addressed.

4.2 Firefighting

The President of the Fire Chiefs' Association of B.C. (FCABC) submitted a report from the Fire Services Liaison Group (FSLG) outlining some serious questions and concerns expressed by its members. Some were addressed, but a significant number still exist.

The Province announced that the changes to the Code had the support of the Office of the Fire Commissioner, a provincially run and funded agency. The request and opportunity for input came after the initial announcement.

It is critical that the safety of the occupants and firefighters be considered in any requirements relating to the construction of any structure. From a Fire Department perspective, these are not mid-rise buildings. They would require high-rise firefighting tactics. The firefighting strategy would have to be further modified, based on the combustible material construction for the reasons previously indicated.

Fire incidents would require an increased resource response to deal with the added tactical requirements compromising the ability of the Fire Department to quickly attack the fire from an offensive stance, in other words, finding the seat of the fire and extinguishing it quickly minimizing the fire loss. This is difficult enough in three storey apartment buildings. If the firefighters are forced into a defensive stance (fighting the fire from outside at a safe distance), they are only able to control the spread of the fire to adjoining exposures and extinguishment is accomplished by "surround and drown" where appliances with large nozzle are set up to pour water on the structure until the fire is out, usually resulting in catastrophic fire loss.

Even with the most up-to-date fire protection systems in place to alert occupants and slow the fire down (i.e. sprinklers), the ability for occupants to escape quickly is probably the most important factor. When an alarm sounds, all too often it is ignored and we usually find only a handful have made their way from the building. In a wooden structure, it is that much more imperative that all occupants get out safely and quickly. If there is a fire emergency, a taller building will take longer to be evacuated and, with our search taking longer to complete, fewer resources will be available initially to begin an offensive fire attack.

For these reasons, the Fire Department would not support proposals allowing wood-frame buildings of more than the current four storey limit and height restriction for these types of structures.

4.3 Permit and Inspection Process

Staff involved in the permit and inspection process of multi-storey residential buildings rely on the expertise of registered professionals, such as architect and engineers, with respect to issues regarding the building envelope, structural adequacy and building material shrinkage. If the architects and engineers are not ready or adequately prepared to deal with the design and construction implications of the six storey wood-frame buildings, staff could not support proposals to construct such buildings.

5.0 CONCLUSION

Although there is support in principle to allow six storey wood-frame building construction, the following technical and process issues remain to be addressed:

- Lack of research on seismic design;
- Fire risks to occupants;

- Firefighting;
- Building Envelope;
- Material Shrinkage;
- Qualification of Design Professionals;
- Qualification of Contractors and Trades; and
- Education and Training for those involved in design and construction

Given the concerns outlined in this report, it is recommended that:

- 1. Rezonings for the development of five or six storey wood-frame buildings only proceed after the concerns outlined in this report have been satisfactorily addressed.
- 2. Council authorize the amendment to the Building Bylaw to include Building Specialists in the definition of Registered Professionals enabling the Chief Building Inspector to require Building Specialists for the design and field review of the construction of complex buildings.
- 3. A copy of this report be sent to Honourable Rich Coleman, Minister of Housing and Social Development, requesting that the issues outlined in this report be addressed for inclusion in the B.C. Building Code.

B. Luksun Director Planning & Building

R. Cook Fire Chief

PS:ap Q:PATRICK\Report\BLD-SIX STOREY WOOD FRAME RES BLDG.doc

cc: Director Engineering City Solicitor Chief Building Inspector Thanks John.

Doug are you available to attend a meeting on the 13th of November for me (see below)?

Stephen R. Gamble, CFO, MIFireE Fire Chief Port Coquitlam Fire & Emergency Services

1725 Broadway Street Port Coquitlam, BC 604.927.5466 (office) 604.927.5472 (direct line) 604.927.5406 (fax)

gambles@portcoquitlam.ca

"This message and any attachments may contain confidential and privileged information. If you are not the intended recipient, please notify the sender immediately by telephone and destroy any copies. Any dissemination or use of this information by a person other than the intended recipient is unauthorized and may be illegal. Thank you."

From: Steve Gamble [mailto:gambles@portcoquitlam.ca]
Sent: Friday, October 31, 2008 2:06 PM
To: Nicol, John HSD:EX
Cc: Fire Chiefs Assoc.
Subject: RE: 6 Storeys Residential Wood Buildings Project
Lhave another meeting scheduled on the 13th which is why

I have another meeting scheduled on the 13th which is why I asked the question. Hopefully you will have the "near final draft" ready for the 7th. If you could let me know ASAP if you don't feel you are going to make the 7th I would appreciate it. I will then try and have someone from our Association attend on my behalf.

SRG

From: Steve Gamble [mailto:gambles@portcoquitlam.ca]
Sent: Friday, October 31, 2008 12:57 PM
To: Nicol, John HSD:EX; dbell@fpoa.bc.ca
Subject: RE: 6 Storeys Residential Wood Buildings Project
John will this be the same information that you will be providing to us next Friday (7th)?

SRG

Hi John

Below are our thoughts for now.

1. Local firefighting capacity

Specific examples and benchmarks would help a local fire dept in evaluating whether they have the capacity and capability.

Examples

Aerial truck requirement Pumping and water flow capacity? Manpower - Need to have X number of fire fighters on scene within X minutes Mutual aid availability and agreement Wildfire interface issues

Two NFPA standards that give information on firefighting capabilities are:

NFPA 1720 Standard for the Organization and Deployment of Fire Suppression Operations, Emergency Medical Operations, and Special Operations to the Public by Volunteer Fire Departments 2004 Edition

NFPA1710 Standard for the Organization and Deployment of Fire Suppression Operations, Emergency Medical Operations, and Special Operations to the Public by Career Fire Departments 2004 Edition

For example;

Volunteer fire departments, they should have 10 firefighters on scene within 10 minutes 80% of the time and start fire operation within 2 minutes of arrival 90% of the time. Career fire departments One minute (60 seconds) for turnout time and Four minutes (240 seconds) or less for the arrival of the first arriving engine company at a fire suppression incident and/or 8 minutes (480

less for the arrival of the first arriving engine company at a fire suppression incident and/or 8 minutes (480 seconds) or less for the deployment of a full first alarm assignment at a fire suppression incident 90% of the time.

- Keep in mind this is for a normal response times to a normal fire situation. Additional resources are required for many types and sizes of buildings within the fire departments response area. Many occupancies and sizes of buildings put additional measures in place knowing that the capability and resources of the local fire department is limited and in many cases the construction of the building is not worth the risk and is not built. This is especially true if we are going beyond the building code.
- 6 storey wood frame the issues are different as well. If all the safety features were included as for any building over 4 stories that would normally be built out of non-combustible materials, the response capability of fighting still could not be met. The thought process would be not only being easier for the fire departments to make that determination but would also be consistent throughout the province.
- Leadership from the province in establishing these guidelines for consideration would be welcomed especially since this is going beyond the building code.
- The final say should still rest with the AHJ but good and accurate information in which to evaluate is necessary.
- 1. **Occupancy** Evaluation on what type of occupancy should not be allowed to occupy the building. 6 storey, wood frame should not be used for what is referred to as assisted living (which is really a boarding or lodging house)
 - 2. **Construction phase** One of the most vulnerable times is during the construction phase. As even the largest fire departments in the province have had very little success with a fire in a 4 storey wood frame under construction (or a 3 storey for that matter).
- There needs to be in place is a standard province-wide template for a fire safety plan for a wood framed building 3 stories or higher under construction.
- Measures in place to limit fire spread in building under construction fire stops, firewalls etc.
- Measures in place to control a fire during construction. Fire extinguishers, standpipes and hose, phasing

Page 13 HOU-2011-00021 in of sprinklers in portions of the building etc.

- Phased construction so that at any one time only a portion of the building is unprotected with fire stops etc.
- Exposures of adjacent buildings and occupancies.

The capacity of most fire departments that are able to review and know what a good fire safety plan is very limited.

Provincial direction would go a long way to take that burden of time and expertise off of the individual fire departments by "re-inventing the wheel".

This would provide useful and high quality plans that work and that can make a difference and that is standard throughout the province.

Very few fire departments have the resources to spend the time in getting a fire safety plan that works but most don't.

The OFC - Interpretation Bulletins, Safety Advisory Bulletins and Information Bulletins have been very useful and provide province wide clarity. Extending this to larger issues such as Fire Safety Plan guidelines for example would be of great help by all fire departments in the province.

Doug Bell

Stephen Gamble, Port Coquitlam Fire Chief is quoted in the article in his role as BC Fire Services Liaison. We read the article before our scheduled meeting with Director of Development Services, Planning Manger and Chief Gamble yesterday to discuss pros, cons and recommendations to Council/Committee.

I welcome any comments in the next week related to Five and Six Storey Residential Wood Frame (56SRWF) code changes. We are going to review with Council or Committee in early March.

Planners generally support densification in most areas noting affordability or additional open space (less site coverage) enhancements. Parking will be significant issue for many sites. We noted a building permit application could be submitted tomorrow for a few sites and therefore Council review should be a priority. Most sites require rezoning.

Fire issues include fire deaths in residential occupancies, fire code and building code not really being companion documents, firefighting in some regional districts not being adequate, number of firefighters available in Poco not to NFPA standard (but not mandatory), multifamily balconies in courtyards (Planners say 5 and 6 storey courtyards are unlikely due to lack of natural lighting) and lack of noncombustible (masonry) stair enclosures. We discussed firefighting concepts, type of construction, mounding to manipulate grade definition, fire separations, fire stopping, damage to fire separations, typical slow response by occupants to evacuate buildings during fire, property damage, seniors, shrinkage, 4 storey residential origins, seismic, APEGBC and AIBC may produce 5/6RWF structural, seismic or envelope guidelines but not sure they are enforceable etc.

Chief Gamble indicated good long term statistics for fire deaths and property damage were/are not maintained.

A few points:

- 1. Exterior cladding enhancements is required for 56SRWF
- 2. The volume of a 6SRWF building is the same as 4SRWF building.
- 3. The 18m height limit permits 6SRWF or 5SRWF with one mezzanine floor.
- 4. All buildings are sprinklered with fast response heads including most balconies
- 5. Commercial floor areas are permitted of noncombustible construction similar to 4SRWF.
- 6. Fire deaths occur in dwellings but it's unlikely fire deaths would increase in dwellings, corridors or exits of apartment buildings because of 56SRWF proposed changes
- 7. Firefighters rescue people and attack fire from inside the building
- 8. They ladder balconies or windows to save occupants if circumstances permit
- 9. There is no code requirement for WFR sprinklered buildings to have balconies or windows for rescue
- 10. I am not aware of any substantial fire issues directly related to proposed height increase for Port Coquitlam (some fire departments may)
- 11. Seniors buildings may have egress problems (we did not discuss but Group B/C changes likely at national level in 2010 code).
- 12. We discussed building bylaw amendments to limit size of buildings to support firefighting. they would have to apply to all buildings, not just 56SRWF. We also noted bylaw amendments may be subject to concurrent authority. We did not pursue this because building's volume is the same with smaller floor plate offset by increased height.

The meeting concluded with Director of DS offering to prepare briefing report to Council. I will have input on the report. At this early stage, I'm not considering bylaw amendments to restrict 56SRWF. Consider means to address following issues:

- 1. Joint and several review by province
- 2. Assisted Living will be permitted in 56SRWF while 2010 National Code reviews 3 storey limit for 2010 NBC
- 3. Seismic shear wall design requires less building articulation including above grade covered parking
- 4. Architect and engineers specialist designations i.e. Structural, Building Envelope Specialist, Certified Professional
- 5. Architect and engineer guidelines are part of regulatory system
- 6. Mounding sites to meet grade and number of storeys requirement
- 7. Improve firestop and fire separation field review/monitoring/inspection
- 8. Sprinklers etc being operational during construction
- 9. Wood shinkage design details and moisture testing from appropriate RP are provided

Thanks

Tim Arthur, P. Eng., CP Manager, Building Permits and Inspections 927-5478

portcoquitlam.ca

This message and any attachments may contain confidential and privileged information. If you are not the intended recipient, please notify the sender immediately by telephone and destroy any copies. Any dissemination or use of this information by a person other than the intended recipient is unauthorized and may be illegal. Thank you.

From: Shek, Patrick [mailto:Patrick.Shek@burnaby.ca] Sent: Friday, January 30, 2009 9:30 AM

To: Beverly Endersby; Al Karimabadi; Bob Thompson; Brett Dwyer; Brian Bydwell; Dave Bruce; edmond.lin@ubc.ca; Frank Durante; Gavin Woo; Greg Yeomans; James Blake; Jim Weber; John de Ruiter; kskulsky@corp.delta.bc.ca; Iholitzki@westvancouver.ca; Lisa Thompson; Manjit Sohi; Nick Marach; Percy Melville; Peter Kushnir; Pieter Den Uyl; Richard Wilson; Robert Cesaretti; Ron Dickinson; Ron North; Stephen Cote-Rolvink; Stephen.butt@gov.bc.ca; Tim Arthur; Trudy Rotgans; William Johnston **Subject:** 6 storey wood frame

Just in case you have not come across this article in the paper here is a copy for your information.

Dat Shek

Patrick Shek, P.Eng., C.P. Chief Building Inspector Building Department, City of Burnaby 4949 Canada Way, Burnaby, B.C. V5G 1 M2

Ph: (604) 294-7158 Fax: (604) 294-7986 Email: patrick.shek@burnaby.ca

The content of this posting or electronic message are solely the writings, thoughts and/or ideas of the account holder and may not necessarily reflect those of the City of Burnaby. If you have any concerns about inappropriate use of this account, please email <u>postmaster@burnaby.ca</u>

The City of Pitt Meadows is looking at passing a resolution to approve Policy to limit the height of wood frame construction to 4 stories due to firefighting capabilities.

Are there any other Cities / Municipalities considering the same?

Please let me know by emailing me directly at bperrie@pittmeadows.bc.ca

Hi Jeff

Sorry, I just missed the deadline but I guess it is better late than never. Here are my comments:

Proposed changes:

Proposed change # 1: Support

Proposed change # 2: Support but I think the floor separation required in 3.2.2.45.(2)(a) should be increased to 1.5 h for 5 and 6 storey buildings. The reason being that a 6 storey office building is required to be non-combustible with 1 h floor separation while a 6 storey apartment with sleeping accommodation is allowed combustible construction with the same 1 h floor separation.

Proposed change #3: (i) Support

(ii) Support

(iii) Not support. The vinyl siding is not equivalent to (i), (ii) and (iv) and does not achieve the same fire protection as the rest. This is a relaxation.
 (iv) Support, but I have not seen the use of fire-retardant treated wood cladding on a building because of the initial cost and maintenance.

Proposed change #4: Support

Proposed change # 5: Support but more time is needed to review and make changes to Part 4. This is just a piece meal solution.

Proposed change # 6: Support but more time is needed to review and make changes to Part 4. This is just a piece meal solution.

Proposed change #7: Support. This is better than wedging the fire door open.

Proposed change #8: Support but more time is needed to review and make changes to Part 4. This is just a piece meal solution.

Ideas for future consideration

A. Horizontal Exiting: 3.4.1.6.(1) restricts horizontal exit to one half of the required number of exits and this should also apply to 5 and 6 storey wood-frame buildings. This requirement should not be relaxed.

B. Why limit the third part review requirement to 6 storey wood-frame buildings? How about those complex buildings? I think this requirement should be at the discretion of the AHJ.

C. Unless the joint and several liability clause is being removed the site inspections by building officials should be at the discretion of AHJ, similar to the field reviews should be at the discretion of the RP

D. There is just not enough time for education and training if these changes are made effective in January. The effective date of the changes should be delayed so that APEGBC would have enough time to develop design guideline for its members. I think some of the municipalities might want to create bylaws requiring

Designated Structural Engineers for the design of Part 3 buildings including 6 storey wood-frame buildings; however, more time is needed in order to do that prior to the implementation of these changes.

Pat Shek

Patrick Shek, P.Eng., C.P. Chief Building Inspector Building Department, City of Burnaby 4949 Canada Way, Burnaby, B.C. V5G 1 M2

Ph: (604) 294-7158 Fax: (604) 294-7986 Email: <u>patrick.shek@burnaby.ca</u>

The content of this posting or electronic message are solely the writings, thoughts and/or ideas of the account holder and may not necessarily reflect those of the City of Burnaby. If you have any concerns about inappropriate use of this account, please email <u>postmaster@burnaby.ca</u>

Hi Roger

I'll be there.

I have a question regarding the implementation of the code change allowing the 6 storey wood frame buildings. At yesterday's meeting on Education and Training John and Bob brought up the possibility of AHJ be able to opt in or opt out of this code change. I don't think this issue was brought up before and I would be interested to hear your clarification.

Pat Shek

Patrick Shek, P.Eng., C.P. Chief Building Inspector Building Department, City of Burnaby 4949 Canada Way, Burnaby, B.C. V5G 1 M2

Ph: (604) 294-7158 Fax: (604) 294-7986 Email: <u>patrick.shek@burnaby.ca</u>

The content of this posting or electronic message are solely the writings, thoughts and/or ideas of the account holder and may not necessarily reflect those of the City of Burnaby. If you have any concerns about inappropriate use of this account, please email <u>postmaster@burnaby.ca</u>

From: Ken Vance [mailto:kvance@civicnet.bc.ca]
Sent: Wednesday, October 1, 2008 10:20 AM
To: Nicol, John HSD:EX
Subject: Re: Six Storey Wood Building Implementation (Local Government) Advisory Group Importance: High
UBCM is interested in participating in this process.

s.22

I would appreciate if you could forward me information from the meetings.

Yours truly

Ken Vance

Hello Trudy and Jeff,

Greetings from the City of Abbotsford. I am very much interested in the development of this proposal. I am not sure who has been selected on the stakeholder group but I believe it to be important that Abbotsford can have a voice on that committee/group. We are the fifth largest community (population wise) and mid-rise apartments are going to be a very popular method of housing for our City. I'll put my name forward to represent the City of Abbotsford in this matter.

The recent fire in Abbotsford and now in Surrey that destroyed large wood frame apartment structures has given me some pause to think. Should we increase the heights of wood frame apartments to the 6 storey level without giving any thought to interim fire protection systems that ought to be installed whilst the large wood frame building are being constructed. The combustible content and fire storm stacking effect has tremendous Limiting distance implications. We have witnessed charring of solid wood posts well over 30 metres away from the apartment building (frame) across a large 4 lane street (Marshall Road). Flames extended to 60 metres in height! The six storey proposal would exponentially add to the tremendous fire intensity and generate a serious fire storm. Is that also being considered and modeled or tested?

Thank you for taking the time to review this email. Best regards, Pieter M. Den Uyl, RBO Manager Building Permits & Licences Division City of Abbotsford Ph: 604-864-5612 Fax: 604-853-5373 Hi All

Since now you have a chance to review all the proposed changes to the code on the 6 storey wood - framed buildings I would like to follow up on the proposal from the City of Surrey regarding a letter to the Branch registering our concerns. Here is a draft for your review. Please send your comment back to me before December 31.

Pat Shek Patrick Shek, P.Eng., C.P. Chief Building Inspector Building Department, City of Burnaby 4949 Canada Way, Burnaby, B.C. V5G 1 M2 Ph: (604) 294-7158 Fax: (604) 294-7986 Email: patrick.shek@burnaby.ca

The content of this posting or electronic message are solely the writings, thoughts and/or ideas of the account holder and may not necessarily reflect those of the City of Burnaby. If you have any concerns about inappropriate use of this account, please email postmaster@burnaby.ca

December 22, 2008

Jeff Vasey Executive Director Building and Safety Policy Branch Office of Housing and Construction Standards PO Box 9844 Stn Prov Govt Victoria, BC V8W 9R3

Dear Sir:

Re: Proposed Changes to the B.C. Building Code

The Province has been very clear in advising that the B.C. Building Code will be amended in January, 2009 to allow six storey wood-frame buildings. We understand that implementation of the proposed changes have been expedited so that they will take effect at the time of the January 2009 adoption. Although the Branch has done a respectable job of studying the issues and obtaining necessary public and industry input, members of the Regional Permits and Licences Committee consider it necessary to register our concerns regarding the abbreviated implementation period.

Local jurisdictions, registered professionals, builders, trades and manufacturers need time to properly deal with the proposed changes. Some Local jurisdictions are exploring amendments to our permitting and inspection processes such as requiring designated structural, building envelope and third party review for all part 3 buildings, including 6 storey wood frame buildings. Time is also required to allow AIBC and APEGBC to establish the building specialists and develop design guidelines and Best Practice guides for their members. While education and training would be required for most of industry participants, architects and contractors would also need education and training to address issues such as shrinkage, and the junction between varying materials.

Accordingly, we request your consideration in delaying implementation of the changes and provide at least a 6-month lead-time between the adoption and the effective date of the proposed changes. In the meantime, members of the Regional Permits & Licenses Committee will be happy to provide whatever assistance we can to facilitate the implementation of those proposed changes.

Yours truly,

Pat Shek

Patrick Shek, P.Eng., C.P. Chair, Regional Permits & Licenses Committee



CITY OF CHILLIWACK OFFICE OF THE MAYOR

May 28, 2008			ESTS AND RANGE
The Honourable Rich Coleman		MRL #:	
Minister Responsible for H	Iousing		
PO Box 9049	/res \	JUN 0 2 2008	
Stn Prov Gov't			1000
Victoria, BC	JUN 0 2 2008	DUE DATE:	
V8W 9E2	ANG VINA	DRAFT REPLY	D DIRECT REDIV
	ALL STR	D FNA D FYI	
Dear Minister Coleman;	PL PESPONSIBLE	 Transition and the second secon	

In May, Premier Gordon Campbell announced his government's support of British Columbia's forest industry by allowing the construction of wood-frame condominiums higher than the current four-storey limit. In addition, as reported in the Vancouver Sun on Tuesday, May 13th, your Ministry advised the Canadian Homebuilders' Association of your support of this initiative.

The City of Chilliwack Council at the their May 20th regular meeting unanimously endorsed a resolution in support of the government's initiative encouraging changes to the BC Building Code that would allow for wood-frame construction up to six (or more) storeys for residential uses.

While continuing to maintain the objectives of the code with respect to structural, safety and fire protection, the City of Chilliwack believes allowing for more than four-storey wood-frame construction, will have a profound and positive effect on our community. It is our belief the more cost-effective use of one of British Columbia's sustainable resources will allow developers the opportunity to be more creative in their building design, as well as receiving the benefits of additional density.

More importantly this initiative could have a profound effect in the supply of much-needed safe, affordable housing for the community by way of a variety of "density bonus" zoning options.

Sincerely,

Clint Hames Mayor

DEPUTY MINISTER'S OFFICE MINISTRY OF HOUSING AND SOCIAL DEVELOPMENT MINISTER OF HOUSING AND SOCIAL DEVELOPMENT History Checked REFERRAL NUMBER: AUG 0 8 2008 MIN D DM D MA D AC D REFER TO: 9 0 JUL 2 9 2008 VICTORIA, BRITISH COLUMBIA **UNION OF** RECEIVED: BRITISH COLUMBIA DRAFT REPLY INFO FILE D MUNICIPALITIES July 23, 2008 REMARK: 1=

Suite 60 10551 Shellbridge Way Richmond British Columbia Canada V6X 2W9 604.270.8226 Fax 604.270.9116 Email: ubcm@civicnet.bc.ca

PRESIDENT SUSAN GIMSE

EXECUTIVE DIRECTOR GARY MACISAAC Honourable Rich Coleman Minister of Housing and Social Development Parliament Buildings Victoria, B.C. V8V 1X4

Dear Minister Coleman:

Re: Six Storey Wood-Framed Construction

The UBCM Executive met on July 18. 2008 and discussed a recent proposal by the province to change the BC Building Code to allow for the construction of six storey wood-framed buildings.

The UBCM Executive after reviewing the matter would indicate cautious support for the proposed six-storey-wood framed construction based on the following measures:

 phased implementation – from four storey, to five storeys on top of one story non-combustible construction;

 informed evidence based decision making – need to consider construction techniques (use of engineered lumber etc.), fire protection issues, enforcement/regulation issues, and potential liability concerns;

 education/training and best practice guidelines for building industry, building officials and fire fighters;

public review of proposed Building Code changes.

The Executive understands that there are potential concerns related to wood shrinkage when constructing six storey wood-framed buildings, particularly when set against a concrete structure such as an elevator shaft. In addition, there are a number of different fire fighting issues that need to be considered, such as the need for ladder trucks, additional firefighters when responding to a fire, and additional firefighting training when dealing with six storey woodframed buildings. We would request that all of these issues be addressed when looking at changes to the BC Building Code to permit the construction of six storey wood-framed buildings.

Sincerely,

Suman Simoe

Susan Gimse President